

Concentrating on audio for 27 years

DSP40I

40W Invisible Speaker

Features

- ➢ Input 100V
- > UL certificated, safe & stable
- ➢ Wide Freq. Response: 100Hz -20 kHz
- ➢ Max SPL:102±2dB
- ➢ High sensitivity:87±2dB
- > Totally invisible, installed in the wall or ceiling
- Excellent sound quality, for installation in high-end places

Description

The DSP40I is a in-wall or in-ceiling speaker of 100 input. The 100v transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible.

Thanks to the special driver unit and special material used in the surface cover, DSP410I can perform with wonderful sound when it is installed inside the wall or ceiling.

Totally invisible. When installed in the wall or ceiling and furnished with paint, the DSP40I can be integrated with the surrounding and be totally invisible.

It is ideal choice for industrial and commercial applications in shopping malls, office building and museums where background music and paging is needed.

Specification

Model	DSP404
Rated Power	30W
Line Voltage	100V
Sensitivity(1M,1W)	87±2dB
Max SPL(1M)	102±2dB
Freq. Resp	100Hz-20kHz
Weight	3.25 kg
Size	300mm×400mm×50mm

Professional Audio Manufacturer





Concentrating on audio for 27 years



FREQ. RESPONSE

(dB SPL、1W、1m)





DISTORTION (THD<1.5% 1W、1m、200Hz~10kHz)

Professional Audio Manufacturer